SAFETY DATA SHEET

1. Identification

Product identifier **Cutting Oil - 340 g**

Other means of identification

Product Code No. 73500 (Item# 1006208)

Recommended use Cutting oil

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Canada Co.

Address 83 Galaxy Blvd
Unit 35 - 37
Toronto, ON M9W 5X6
Canada

Telephone

General Information 416-847-7750

24-Hour Emergency (CHEMTREC) 800-424-9300 (Canada)

Website www.crc-canada.ca

E-mail Support.CA@crcindustries.com

2. Hazard identification

Physical hazards Flammable aerosols — Category 1
Gases under pressure — Liquefied gas

Health hazards Not classified.

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

Precautionary statement

Prevention Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Response Wash hands after handling.

Storage Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	65 - 85
liquefied petroleum gas		68476-86-8	10 - 30

Chemical name	Common name and synonyms	CAS number	%
sodium sulfate		7757-82-6	1 - 5
lubricating oils, petroleum, hydrotreated spent		64742-58-1	0.5 - 1.5
distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	0.1 - 1
distillates (petroleum), hydrotreated light paraffinic		64742-55-8	0.1 - 1
distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	0.1 - 1
distillates (petroleum), solvent-dewaxed light paraffinic		64742-56-9	0.1 - 1

The exact percentage (concentration) of composition has been withheld as a trade secret.
All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact No adverse effects due to skin contact are expected.

Eye contact No specific first aid measures noted.

Ingestion In the unlikely event of swallowing contact a physician or poison control center.

Most important symptoms/effects, acute and delayed Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical Contents under pressure. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol. Contents under pressure.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

ACGIH

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.
lubricating oils, petroleum, hydrotreated spent (CAS 64742-58-1)	TWA	5 mg/m3	Inhalable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	1 mg/m3	Mist.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	0.2 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	1 mg/m3	Mist.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.
lubricating oils, petroleum, hydrotreated spent (CAS 64742-58-1)	TWA	5 mg/m3	Inhalable fraction.

Canada - Ontario

Components	Type	Value
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3
	TWA	5 mg/m3

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	TWA	5 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
lubricating oils, petroleum, hydrotreated spent (CAS 64742-58-1)	TWA	5 mg/m3	Inhalable fraction.

Canada - Quebec

Components	Type	Value
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3
	TWA	5 mg/m3

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	15 minute	10 mg/m3
	8 hour	5 mg/m3
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	15 minute	10 mg/m3
	8 hour	5 mg/m3
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	15 minute	10 mg/m3
	8 hour	5 mg/m3
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	15 minute	10 mg/m3
	8 hour	5 mg/m3
distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	15 minute	10 mg/m3
	8 hour	5 mg/m3

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Neoprene.
Other	Wear suitable protective clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Brown.
Odor	Mild petroleum.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-40 °F (-40 °C) estimated
Initial boiling point and boiling range	500 °F (260 °C) estimated
Flash point	316.4 °F (158.0 °C) Pensky-Martens Closed Cup
Evaporation rate	Slow.
Flammability (solid, gas)	Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapor pressure	2979.2 hPa estimated
Vapor density	> 5 (air = 1)
Relative density	0.85

Solubility(ies)

Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	600 °F (315.6 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.

Other information

Percent volatile	95.5 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides. Sulfur oxides. Mercaptans. Sulfides. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Ingestion	Based on available data, the classification criteria are not met.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components	Species	Test Results
distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	A4 Not classifiable as a human carcinogen.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	A4 Not classifiable as a human carcinogen.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	A4 Not classifiable as a human carcinogen.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	A4 Not classifiable as a human carcinogen.
distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	A4 Not classifiable as a human carcinogen.
lubricating oils, petroleum, hydrotreated spent (CAS 64742-58-1)	A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Not classifiable as a human carcinogen.
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	Not classifiable as a human carcinogen.
distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Not classifiable as a human carcinogen.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Not classifiable as a human carcinogen.

distillates (petroleum), solvent-dewaxed light paraffinic (CAS 64742-56-9)	Not classifiable as a human carcinogen.
lubricating oils, petroleum, hydrotreated spent (CAS 64742-58-1)	Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	3 Not classifiable as to carcinogenicity to humans.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Possible reproductive hazard.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
Cutting Oil - 340 g			
Aquatic			
Crustacea	EC50	Daphnia	1394.0469 mg/l, 48 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Dispose in accordance with all applicable regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

UN number UN1950
UN proper shipping name AEROSOLS, flammable, Limited Quantity
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Packing group -
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1950
UN proper shipping name Aerosols, flammable, Limited Quantity
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Packing group -
ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name AEROSOLS, Limited Quantity

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Packing group -


Environmental hazards

Marine pollutant No.


EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA



IMDG; TDG



15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	09-03-2019
Revision date	04-14-2021
Version #	02
Further information	CRC # 574/1002598
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Canada Co..
Revision information	This document has undergone significant changes and should be reviewed in its entirety.